Permanent ink PP170*, SP117*, PCM Bases*, Wood shade inks

*see section 16 for colour names

Data Sheet No: DS504 Version No: 001

Issue Date: 15th April 2019 Actualization: 15th April 2019 Page 1

1.0- Identification of the substance/mixture and of the company/undertaking

1.1 - Product Identification

Trade name: Permanent ink PP170*, SP117*, PCM Bases*, Wood shade inks

Substance name: n/a
Index No: n/a
CAS-No: n/a
EC-No: n/a

1.2 - Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture: Preparation for use in writing instruments

Recommended restrictions on use: No information available

1.3 - Details of the suppler of the safety data sheet

Company : Kores Europe s.r.o.

Nivka 336, 378 53 Strmilov

Czech Republic

Contact customer service: 1190 Vienna, AUSTRIA

Telephone : +43/1/3780755

web : www.kores.com
e-mail addresse : kores@kores.at

1.4 – Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964	
United Kingdom	National Poisons Information Service (NHS Direct)	http://www.npis.org	111 (England & Wales only) or 112 (EU) or 08454 24 24 24 (Scotland)	

2.0 - Hazards Identification

2.1 - Classification of the substance or mixture

Regulation (EC) No. 1272/2008			
Hazard class	Hazard category	Target organs	Hazard statements
Flammable liquids	2	n/a	H225
Sensitising	1B	skin	H317
Serious eye damage/eye irritation	2	eyes	H319
STOT-SE	3	CNS	H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

Permanent ink PP170*, SP117*, PCM Bases*, Wood shade inks

*see section 16 for colour names

Data Sheet No: DS504 Version No: 001 Issue Date: 15th April 2019 Actualization: 15th April 2019 Page 2

Most important adverse effects: Highly flammable liquid and vapour. Causes serious eye irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness.

2.2 - Label Elements

Labelling according to Regulation (EC) No. 1272/2008

Hazard Symbols:

Signal word: DANGER

Hazard statements: H225 Highly flammable liquid and vapour

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

Precautionary statements: P210 Keep away from heat/sparks/open flames/hot surfaces. No

smoking

P233 Keep container tightly closed

P240 Ground/bond container and receiving equipment P243 Take precautionary measures against static discharge P280 Wear protective gloves/protective clothing/eye protection P303/P361/P352/P353 IF ON SKIN: remove immediately all contaminated clothing. Wash with plenty of soap and water P305/P351/P338 IF IN EYES: rinse cautiously with water for several minutes Remove contact lenses, if present and easy to

do. Continue rinsing

P333/P313 If skin irritation or rash occurs: get medical

advice/attention

P337/P313 If eye irritation persists: get medical

advice/attention

P403/P235 Store in a well-ventilated place. Keep cool.

2.3 - Other hazards

The material does not meet the criteria for PBT or vPvB in accordance with Annex XIII of the REACH Regulation.

3.0 - Composition / information on ingredients

3.1 - Substances

Chemical nature: mixture

Permanent ink PP170*, SP117*, PCM Bases*, Wood shade inks

*see section 16 for colour names

Data Sheet No: DS504 Version No: 001 Issue Date: 15th April 2019 Actualization: 15th April 2019 Page 3

Chemical name	REACH Reg. No.	CAS No.	EC No.	Amount (%)
1-Methoxy-2-propanol	01-2119457435-35	107-98-2	203-539-1	<75%
Propan-2-ol	01-2119457558-25	67-63-0	200-661-7	<20%
Solvent Yellow 21		5601-29-6	227-022-5	<6%
2-amino-2-methylpropanol	01-2119475788-16-xxxx	124-68-5	204-709-8	<1%

Chemical name	Classification according to Regulation (EC) No. 1272/2008
1-Methoxy-2-propanol	H226 (3), H336 (3)
Propan-2-ol	H225 (2), H319 (2), H336 (3)
Solvent Yellow 21	H317 (1B), H319 (2), H412 (3)
2-amino-2-methylpropanol	H315 (2), H319 (2), H412 (3)

For the full text of the H-Statements mentioned in this Section, see Section 16.

4.0 - Description of first aid measures

4.1 - Description of first aid measures

General advice: Take off all contaminated clothing immediately

In case of inhalation: Remove to fresh air. If symptoms persist, seek medical

advice. If unconscious place in recovery position

In case of skin contact: Wash off with plenty of water. If skin irritation persists,

seek medical advice

In case of eye contact: Rinse thoroughly with plenty of water, also under the eyelids.

Consult an eye specialist immediately

4.2 - Most important symptoms and effects, both acute and delayed

No information available

4.3 - Indication of immediate medical attention and special treatment needed

Treat symptomatically. No further information available

5.0 - Firefighting measures

5.1 - Extinguishing media

Suitable extinguishing media:

Use water spray, alcohol-resistant foam, dry chemical or carbon

dioxide

Unsuitable extinguishing media: High volume water jet

5.2 - Special hazards arising from the substance or mixture

Specific hazards during fire-fighting: Highly flammable. Vapours may form explosive mixtures

with air. In case of fire hazardous decomposition

Permanent ink PP170*, SP117*, PCM Bases*, Wood shade inks

*see section 16 for colour names

Data Sheet No: DS504 Version No: 001 Issue Date: 15th April 2019 Actualization: 15th April 2019 Page 4

products may be produced, such as carbon monoxide (CO) and carbon dioxide (CO_2).

5.3 - Advice for firefighter

Special protective equipment for firefighters: In the event of fire, wear self-contained

breathing apparatus. Wear appropriate body

protection (full protective suit)

Further information: Cool closed containers exposed to fire with

water spray. Heating will cause a pressure rise – with risk of bursting. Collect contaminated fire extinguishing water separately. This must not

be discharged into drains

6.0 – Accidental release measures

6.1 – Personal precautions, protective equipment and emergency procedures

Personal precautions: Use personal protective equipment. Provide adequate

ventilation. Keep away from heat and sources of ignition. Avoid

contact with skin and eyes. Do not breathe vapours.

6.2 - Environmental precautions

Environmental precautions: Do not flush into surface water or sanitary sewer system. Avoid

subsoil penetration

6.3 - Methods and materials for containment and cleaning up

Procedure: Contain spillage, and then collect with non-combustible

absorbent material (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local/national regulations (see Section 13)

Further information: Treat recovered material as described in Section 13

6.4 - Reference to other sections

For personal protection see Section 8

7.0 - Handling and storage

7.1 – Precautions for safe handling

Advice on safe handling: Keep container tightly closed. Ensure adequate ventilation.

Avoid contact with skin and eyes. Do not breathe vapours. Emergency eye wash fountains and emergency showers should

be available in the immediate vicinity

Permanent ink PP170*, SP117*, PCM Bases*, Wood shade inks

*see section 16 for colour names

Data Sheet No: DS504 Version No: 001 Issue Date: 15th April 2019 Actualization: 15th April 2019 Page 5

Hygiene measures: Keep away from food, drink and animal feeding stuffs. Smoking,

eating and drinking should be prohibited in the application area. Wash hands before breaks and at the end of the working day. Take off all contaminated clothing immediately. Avoid contact with skin and eyes. Do not breathe vapours of spray mist

7.2 - Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers: Keep in an area equipped with solvent resistant

flooring. Store in original container

Advice on protection against fire and explosion: Combustible liquid. Keep away from sources of

ignition – no smoking. Take measures to prevent the build-up of electrostatic charge. Vapours may form explosive mixtures in air. Use only in an area containing explosion proof

equipment

Further information on storage conditions: Keep tightly closed in a dry and cool place. Keep

in a well-ventilated place. Keep away from heat.

Keep away from direct sunlight

Advice on common storage: Incompatible with oxidizing agents. Keep away

from food, drink and animal feeding stuffs

7.3 – Specific end uses

Specific uses(s): No information available

8.0 – Exposure controls/personal protection

8.1 - Control parameters

1-methoxy-2-propanol (CAS No. 107-98-2)

Regulatory basis: UK. EH40 Workplace Exposure Limits (WELs)

Regulatory list: EH40 WEL

Value type: Time Weighted Average (TWA)

Value: 100 ppm Value: 375 mg/m^3

Regulatory basis: UK. EH40 Workplace Exposure Limits (WELs)

Regulatory list: EH40 WEL

Value type: Short Term Exposure Limit (STEL)

Value: 150 ppm Value: 560 mg/m³

Regulatory basis: EU. Indicative Exposure Limit Values in Directives

91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Value type: Short Term Exposure Limit (STEL)

Value: 150 ppm Value: 568 mg/m³

Permanent ink PP170*, SP117*, PCM Bases*, Wood shade inks

*see section 16 for colour names

Data Sheet No: DS504 Version No: 001 Issue Date: 15th April 2019 Actualization: 15th April 2019 Page 6

Regulatory basis: EU. Indicative Exposure Limit Values in Directives 91/322/EEC,

2000/39/EC, 2006/15/EC, 2009/161/EU

Value type: Short Term Exposure Limit (TWA)

Value: 100 ppm
Value: 375 mg/m³
Regulatory basis: ELV (IE)
Regulatory list: Indicative OELV

Value type: Short Term Exposure Limit (STEL)

Value: 150 ppm
Value: 568 mg/m³
Regulatory basis: ELV (IE)

Regulatory list: Indicative OELV

Value type: Time Weighted Average (TWA)

Value: 100 ppm Value: 375 mg/m³

Propan-2-ol (CAS No. 67-63-0)

Regulatory basis: UK. EH40 Workplace Exposure Limits (WELs)

Regulatory list: EH40 WEL

Value type: Time Weighted Average (TWA)

Value: 400 ppm Value: 999 mg/m^3

Regulatory basis: UK. EH40 Workplace Exposure Limits (WELs)

Regulatory list: EH40 WEL

Value type: Short Term Exposure Limit (STEL)

Value: 500 ppm Value: 1250 mg/m^3

8.2 - Exposure controls

Engineering measures: Refer to protective measures listed in Sections 7 and 8
Respiratory protection: Required, if exposure limit is exceeded (e.g. OEL). Respirator

with a gas filter. Recommended filter type: AX

Hand protection: Wear suitable gloves. Take note of the information given by the

producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Protective gloves should be replaced at first signs of wear. Butyl rubber, 0.5mm, Fluorocarbon rubber, 0.4mm

Eye protection: Tight fitting safety goggles

Skin and body protection: Wear suitable protective clothing

Environmental protection: Do not let product enter drains. If the product contaminates

rivers and lakes or drains inform respective authorities

9.0 – Physical and chemical properties

9.1 - Information on basic physical and chemical properties

Permanent ink PP170*, SP117*, PCM Bases*, Wood shade inks

*see section 16 for colour names

Data Sheet No: DS504 Version No: 001 Issue Date: 15th April 2019 Actualization: 15th April 2019 Page 7

Appearance: Various colours, liquid

Odour: Alcohol-like
Odour threshold: No data available
pH: No data available

Melting point / freezing point: -89.5°C Initial boiling point/boiling range: 82°C Flash point: 12°C

Evaporation rate:

Flammability:

Upper/lower flammability or explosive limits:

Vapour pressure:

Vapour density:

Relative density:

No data available

No data available

No data available

No data available

Solubility: Miscible in water, readily miscible with solvents

Partition coefficient: n-octanol/water: No data available

Auto-ignition temperature: 425°C

Decomposition temperature:

Viscosity:

Explosive properties:

Oxidising properties:

No data available

No data available

No data available

No data available

9.2 - Other information

No further information available

10.0 - Stability and reactivity

10.1 - Reactivity

Advice: Stable under recommended storage conditions

10.2 - Chemical Stability

Advice: Stable under normal conditions

10.3 - Possibility of hazardous reactions

Hazardous reactions: No information available

10.4 - Conditions to avoid

Conditions to avoid: Heat, flames and sparks

10.5 - Incompatible materials

Materials to avoid: Alkali metals, alkaline earth metals, strong oxidizing agents,

nitric acid, sulphuric acid, peroxides (e.g. hydrogen peroxide)

Permanent ink PP170*, SP117*, PCM Bases*, Wood shade inks

*see section 16 for colour names

Data Sheet No: DS504 Version No: 001 Page 8

Issue Date: 15th April 2019 Actualization: 15th April 2019

10.6 - Hazardous decomposition products

Hazardous decomposition: Under fire conditions: carbon monoxide (CO), carbon

dioxide (CO₂)

11.0 - Toxicological information

11.1 - Information on toxicological effects

1-methoxy-2-propanol (CAS No. 107-98-2)

Oral

Value type: LD50

Value: 4016 mg/Kg

Species: rat

Inhalation

Value type: LC50 Value: >25.8 mg/L

Exposure time: 6 h Species: rat

Dermal

Value type: LD50

Value: >2000 mg/Kg

Species: rabbit

Propan-2-ol (CAS No. 67-63-0)

Oral

Value type: LD50 Value: 5840 mg/Kg

Species: rat

Inhalation

Value type: LC50 >25 mg/L Value: Exposure time: 6 h Species: rat

Dermal

Value type: LD50

Value: >13900 mg/Kg

Species: rabbit

12.0 - Ecological information

12.1 - Toxicity

1-methoxy-2-propanol (CAS No. 107-98-2)

Fish

Species: Pimephales promelas (fathead minnow)

Value type: LC50 Value: 20800 mg/lL

Permanent ink PP170*, SP117*, PCM Bases*, Wood shade inks

*see section 16 for colour names

Data Sheet No: DS504 Version No: 001 Issue Date: 15th April 2019 Actualization: 15th April 2019 Page 9

Exposure time: 96 h
Daphnia and other aquatic invertebrates

Species: daphnia magna

Value type: LC50

Value: 21100 - 25900 mg/L

Exposure time: 48 h

Algae

Species: Chlorella vulgaris (Fresh water algae)

Value type: EC50 Value: >1000 mg/L

Exposure time: 7 d

Bacteria

Species: activated sludge

Value type: IC50 Value: 1000 mg/L

Exposure time: 3 h

Propan-2-ol (CAS No 67-63-0)

Fish

Species: Pimephales promelas (fathead minnow)

Value type: LC50
Value: 9640 mg/L
Exposure time: 96 h
Daphnia and other aquatic invertebrates

Species: daphnia magna

Value type: EC50
Value: 9714 mg/L
Exposure time: 24 h

Algae

Species: Scenedesmus subspicatus

Value type: EC50
Value: >100 mg/L
Exposure time: 72 h

Bacteria

Value type: EC50

Value: >100 mg/L, no harming action

12.2 - Persistence and biodegradability

No data available

12.3 - Bioaccumulative potential

No data available

Permanent ink PP170*, SP117*, PCM Bases*, Wood shade inks

*see section 16 for colour names

Data Sheet No: DS504 Version No: 001
Issue Date: 15th April 2019 Actualization: 15th April 2019 Page 10

12.4 - Mobility in soil

Mobile in water environment

12.5 - Results of PBT and vPvB assessment

No data available

12.6 - Other adverse effects

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.

13.0 - Disposal considerations

13.1 - Waste treatment methods

Product: Disposal together with normal waste is not allowed. Special

disposal required according to local regulations. Do not empty

into drains. Contact waste disposal services

Contaminated packaging: Empty contaminated packaging thoroughly. They can be

recycled after thorough and proper cleaning. Packaging that cannot be cleaned is to be disposed of in the same manner as the product. Do not burn, or use a cutting torch on the empty

drum. Risk of explosion

14.0 - Transport Information

14.1 - UN Number

1993

14.2 - UN proper shipping name

ADR: Flammable Liquid n.o.s (contains iso-propanol)
RID: Flammable Liquid n.o.s (contains iso-propanol)
IMDG: Flammable Liquid n.o.s (contains iso-propanol)

14.3 - Transport hazardous class(es)

Labels/classification code/ hazard identification number /tunnel restriction code

ADR: 3; F1; 33: (D/E)
RID: 3; F1; 33
IMDG: 3; (F-E, S-E)

14.4 - Packing group

ADR: II RID: II

Permanent ink PP170*, SP117*, PCM Bases*, Wood shade inks

*see section 16 for colour names

Data Sheet No: DS504 Version No: 001 Issue Date: 15th April 2019 Actualization: 15th April 2019 Page 11

IMDG: II

14.5 - Environmental hazards

Labelling according to 5.2.1.8 ADR:

Labelling according to 5.2.1.8 RID:

No
Labelling according to 5.2.1.6.3 IMDG:

No
Classification as environmentally hazardous according to 2.9.3 IMDG:

No
Classified as 'P' according to 2.10 IMDG:

No

14.6 - Special precautions for user

Not applicable

14.7 - Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IMDG: Not applicable

15.0 – Regulatory Information

15.1 – Safety, health and environmental regulations/legislation specific for the substance or mixture

All components are REACh registered or are exempt from REACh registration
Our inks do not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH),
Article 57)

All components are listed on TSCA list of active substances

15.2 - Chemical safety assessment

No information available

16.0 – Other Information

16.1 - Full text of H-Statements referred to under Sections 2 and 3

H225: Highly flammable liquid and vapour
H226: Flammable liquid and vapour
H315: Causes skin irritation
H317: May cause an allergic skin reaction
H319: Causes serious eye irritation
H336: May cause drowsiness or dizziness

H412: Harmful to aquatic life with long lasting effects

16.2 - Further information

Permanent ink PP170*, SP117*, PCM Bases*, Wood shade inks

*see section 16 for colour names

Other:

Data Sheet No: DS504 Version No: 001

Issue Date: 15th April 2019 Actualization: 15th April 2019 Page 12

Colour names: Black, Black 143A, Yellow, Yellow 48, Brown, Light Brown,

Brown 35, Golden Orange, Golden Orange 33, Aqua, Green 64A, Turquoise 58H, Red 10-42A, Red, Red 143C, Bright Red, Dark Red, Scarlet, Orange, Orange 58K, Pink, Pink 34, Lavender, Violet, Purple 58J, Sky Blue, Cherry Red, Clear Base, Black Base, Orange Base, Yellow Base, Aqua Base, Red, Base, Pink Base The information provided in this safety data sheet is correct to

our knowledge at the date of its revision. The information given only describes the products with regard to safety arrangements

and is not to be considered as a warranty or quality

specification and does not constitute a legal relationship. The information contained in this safety data sheet relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any

process, unless specified in the text

Date of issue of safety data sheet: 15. 4. 2019		
Revision history:		
Version	Date	Changes

HS Tariff code: 32159070